

## PLANK 220 SPECIFICATION SHEET

Atelier Collection Engineered T&G plank by Forté. 15mm thick, 220mm wide, 2200mm length. Glue down installation method onto substrate. Pre-finished with UV Cured Matte Lacquer.

#### PRODUCT DETAILS

Collection Atelier

Product Type Engineered Plank

Availability Stocked
Total Thickness 15mm
Width 220mm
Length 2200mm
% of Shorts Up to 20%

Wear Layer 4mm Solid European Oak
Core Eucalyptus Plywood core

& backing

Construction 2-layer Engineered

Re-sands Up to 2 (approx. 1mm removed per

re-sand)

Surface Texture Brushed Surface Sheen Matte

Bevel Long Edges
Status Pre-finished

(no additional coats required)

Finish Ageing Stain with UV Cured Matte

Lacquer

Species European Oak

Wood Grade Rustic (refer page 2 for details)
Filler Colour Dependant on colour, visit

forte.co.nz for accurate filler colour

The Atelier Collection is also available in planks and selected herringbone and chevron colours.

#### STRUCTURAL WARRANTY

10 Year Commercial For terms and conditions see25 Year Residential www.forte.co.nz/warranties









Dolomite

Siltstone

Classic

Marl



Granite

#### SUSTAINABILITY

#### **Sustainably Sourced**

#### INSTALLATION

Installation Method	Glue down
	(Double Stick for Multi-level)
Suitable Substrates	Plywood, Particle Board, Concrete,
	existing timber - enquire for others
Joint Profile	Tongue and Groove (4 sides)
Suitable Applications	Flooring, Walls, Ceilings
Suitable Uses	Residential homes, hospitality, retail
	stores, restaurants, apartments
Underfloor Heating	<ul> <li>Hydronic Systems</li> </ul>
	· Electric Systems set in screed
	(Ensure screed is suitable for UFH)
	<ul> <li>Enquire for other systems</li> </ul>
Wet Area Suitability	Contact the Forté team for information

0508 35 66 77

#### TECHNICAL SPECIFICATIONS

Reaction to Fire (Floors) Critical Flux 2.2kw/m<sup>2</sup>

Reaction to Fire (Walls	Group 3 / Class Dfl-s1 (Group 1 can
and Ceilings)	be achieved with intumescent coating)
Formaldehyde Emission	
AS/NZS 2098.11	E0 (0.13 mg/L)
	Low VOC, No added Formaldehyde
Wear Layer Density	650kg/m³
Slip Ratings	
AS/NZS 4586 Wet Test	Classification F, Mean COF 0.85
AS/NZS 4586 Dry Test	Classification X, Pendulum Mean 42
	RPN

#### PACK INFORMATION

Pack Size 2.42m²
Pack Weight 24.3kg

Pieces per pack 4 full planks + up to 1 split plank



### ATELIER - RUSTIC GRADE



An Atelier rustic grade plank will typically contain unlimited natural colour variation. This grade allows for more frequent, larger knots and more sapwood should be expected throughout the planks. Cracks and checks will be present and are finished with filler.

### **Care and Maintenance**

RESIDENTIAL AND COMMERCIAL CARE AND MAINTENANCE

Forté's Product Specialists have collated our care and maintenance recommendations to ensure your flooring looks like new for years to come. Residential and Commercial projects require different levels of care and maintenance. Visit www.forte.co.nz/careandmaintenance

# **Structural Warranty**

ATELIER 25 YEAR RESIDENTIAL STRUCTURAL WARRANTY

The Atelier Collection comes with a full 25 year Residential Structural Warranty. For full warranty terms and conditions, please visit www.forte.co.nz/warranties

ATELIER 10 YEAR COMMERCIAL STRUCTURAL WARRANTY

The Atelier Collection comes with a full 10 year Commercial Structural Warranty. For full warranty terms and conditions, please visit www.forte.co.nz/warranties

## **Installation**

THE ATELIER COLLECTION MUST BE INSTALLED BY A TRAINED PROFESSIONAL

Please ensure that you have read and understood the installation guidelines before proceeding to install Atelier timber flooring. If you have any questions or concerns, please call the Forté technical team on 0508 35 66 77. Failure to adhere to the Forté Installation Guidelines may void your warranty.

For full installation guidelines, please visit www.forte.co.nz/installation

